

## Overview


Stokbord is manufactured from recycled polyethylene and has a textured surface which does not show scuff marks. The embossed surface gives good scratch resistance. The standard and most used colour is black.

It is pressure and steam cleanable, non absorbent and maintenance free as it does not require painting.

Kylix recycled plastic sheet has been proven over many years and is widely used across a range of applications.

Normally available in standard 2440x 1220mm wide boards and can be cut, routed, welded and shaped to practically any form using standard methods and techniques.

The following guidance may assist in determining suitability for your application.



## Key benefits

- Highly versatile and suitable for many applications
- Easy to fabricate by routing, cutting and shaping
- Tough, durable and long lasting with lower whole life costs compared to timber
- Maintenance free. Will not need painting or treating during its lifetime
- Rot proof, chew resistant, and non-toxic to animals
- Can be pressure washed and steam cleaned. Highly resistant to many chemicals
- Manufactured from 100% recycled materials. Can be recycled at the end of the application's lifetime
- Highly durable and hard wearing with good impact strength.
- Hygienic - easily cleaned with steam or pressure hose.
- Non-absorbent and chew resistant when used in agricultural environments.
- A good DIY material, easy to handle and work.



## Fixing Instructions

Recommendations for installing Stokbord taking account of the thermal expansion and contraction characteristics of plastic sheet.

1. Where possible, store the sheet at ambient temperature and in the environment it will be used for around 24hrs prior to installation.
2. Pre-drill holes before installation and preferably oversize holes by a min of 2mm in relation to the fixings.
3. Do not use countersunk screws. Use round headed screws or a washer and bolt system.
4. Don't over tighten the fixing to allow for expansion.
5. Do not use nails for fixing sheet
6. Work from top to bottom when inserting fixings.
7. Glue isn't normally recommended, but there are some adhesives on the market that may be used. Check suitability if you intend to use such products.
8. Recycled sheet is weldable but specialised equipment or materials may be required. Contact Kylix UK Ltd for advice.



*A close-up of the AB tek screw with the 29mm washer in place*